

BUILT TO LAST PERFORMANCE























- 10 Gauge Sides and Floor
- 24" High Sides
- 6'-9-1/2" and 6'-1-1/2" Inside Bed Widths
- 8" Cold Formed I Beam Frame

- Rubber Ride Axles
- Aluminum Tool Box w/Storage
- Scissors Hoist on 12' and 14' Lengths
- 11 Gauge Diamond Plate Fenders



Aluminum Tool Box with Storage Area (steel box on gooseneck)



Heavy Duty Adjustable Coupler (4 bolt)



Scissors Hoist Standard on 12' & 14' (cylinder on 10')



Step for Bed Access



Tarp Option



Wider Ramps



Hydraulic Jack Option



Gate Hold Backs



Trip Lever Option



8" I Beam Frame



1/8" Fenders



Bumper Pull

12'

14'

81-1/2"

81-1/2"

STANDARD SPECIFICATIONS

sidewalls & floor	10 gauge (thickness of steel)		
height of sidewall	24"		
width inside body	73-1/2" & 81-1/2"		
frame	8" cold formed I-beam		
tool box	aluminum diamond plate w/storage area		
gate	double acting with metering chains		
fenders	1/8" steel diamond plate		
hydraulic lift	scissors hoist 12' & 14' - cylinder 10'		
hydraulic pump	power up/gravity down		
suspension	rubber ride (low maintenance)		
brakes	electric (all wheels)		
tires & wheels	9950 GVWR - 15" 8 ply rated - 6 bolt		
(all tires are radial)	12000 & 14000 GVWR 16" 10 ply rated		
	8 bolt		
jack	7000 lb. 10' & 12' - 10000 lb. 14'		
coupler	2-5/16" adjustable (4 bolt)		
safety chains	3/8" with latch hook		
lights & wiring	LED lights & sealed wire harness		
ramps	15-1/2" wide x 72" long		
warranty	2 year limited (see warranty for details)		
other standard features	step to access inside bed		
	d-rings inside bed		
	gate hold back latches		
OPTIONS			
available rating	9950, 12000, 14000 & 16000 GVWR		
pintle ring			
tarp			
stake pockets			
trip lever (forward pull)	for tailgating		
jack upgrade	7k to 10k (10k standard on 14' bumper		

pulls and all goosenecks)

black - red - charcoal

operates hydraulics wirelessly

hydraulic jack (power up/power down)

jack upgrade

wireless remote

pallet fork holders

spare tire & wheel

DUMP BODY VOLUME

length	width	volume (cubic yard)
10'	73-1/2"	4.5
10'	81-1/2"	5
12'	81-1/2"	6
14'	81-1/2"	7

AXLE SPECIFICATIONS (rubber ride suspension)

GVWR	axle
9950	6000 lb - 6 bolt - electric brakes & easy lube spindles
12000	6000 lb - 8 bolt - electric brakes & easy lube spindles
14000	7000 lb - 8 bolt - electric brakes & easy lube spindles
16000	8000 lb - 8 bolt - electric brakes & oil bath hubs

4430 lbs

4740 lbs

4590 lbs

4900 lbs

5010 lbs

5320 lbs

FRAME & BODY SPECIFICATIONS

3580 lbs

n/a

frame & tongue	body sides & floor	body cross members	body main rails	fenders
8" @ 10 lb/ft I-beam (cold formed)	10 gauge	3" channel	2" x 3" x 3/16" tube	1/8" diamond plate

WEIGHT SPECIFICATIONS by GVWR (gross vehicle weight rating)

3990 lbs

4140 lbs

3840 lbs

3980 lbs

length width 9950 GVWR 12000 GVWR 14000 GVWR 16000 GVWR length width 12000 GVWR 14000 GVWR 16000 GVWR 73-1/2" 3140 lbs 10' 3400 lbs n/a n/a n/a n/a n/a n/a n/a 81-1/2" 3420 lbs 3580 lbs 10' n/a n/a n/a n/a n/a n/a n/a

4410 lbs

4560 lbs

Gooseneck

12'

14'

81-1/2"

81-1/2"

MORITZ TRAILERS & TRUCK BODIES	MORITZ INTERNATIONAL, INC. 665 North Main Street, Mansfield, Ohio 44902 Phone (419)526-5222 www.moritzint.com
NAME OF THE PARTY	
MEAVY COMMERCIAL	RITZ
© 2014 Moritz International, Inc. design, specifications, and prices are subject to change without not	