

BUILT TO LAST PERFORMANCE

























Cold Formed 8" I Beam



Aluminum Tool Box



Hydraulic Tail with Autolock System



Tie Down Slot in Tail



Tie Down Between Fenders (flush w/deck & fenders)





Heavy Duty 4" x 1/4" Bar Stake Pockets



Step To Access Deck



Heavy Duty 4 Bolt Adjustable Coupler



Optional Fender Tool Boxes (ratchet boomer storage)



Optional Hydraulic Jack

### STANDARD SPECIFICATIONS

deck height	22" to 23"			
between fenders	81-1/2"			
frame	8" cold formed I-beam			
stake pockets	4" x 1/4" formed bar			
tool box	aluminum diamond plate			
Hydraulic Tail	66" long			
Loading Angle	18 degrees			
fenders	1/8" steel diamond plate			
suspension	rubber ride (low maintenance)			
brakes	electric (all wheels)			
tires & wheels				
12000 lb & 14000	lb GVWR - 16" 10 ply rated 8 bolt			
16000 lb GVWR -	17.5" 16 ply rated 8 bolt			
jack	12000 lb			
coupler	2-5/16" adjustable (4 bolt)			
safety chains	3/8" with latch hook			
lights & wiring	LED lights & sealed wire harness			
2 year limited warra	nty (see warranty for details)			

#### **OPTIONS**

OF HONS			
fenders with built in tool boxes			
hydraulic jack			
pintle ring			
wireless remote control			
winch mount			
winch mount with 8000 lb. electric winch			
pallet fork holder			
spare tire & wheel			
COLORS	black - red - charcoal		

### FRAME SPECIFICATIONS

frame & tongue		cross r	members		fenders		
one piece cold f	one piece cold formed 8" I-beam		on 16" centers	1/8" steel diamond plate			
20' Bumper Pull		22' Bun	nper Pull	All G	All Goosenecks		
GVWR	beam specs	GVWR	beam specs	GVWR	beam specs		
12000	8" @ 10 lb/ft	12000	8" @ 15 lb/ft	12000	8" @ 15 lb/ft		
14000	8" @ 10 lb/ft	14000	8" @ 15 lb/ft	14000	8" @ 15 lb/ft		
16000	8" @ 15 lb/ft	16000	8" @ 15 lb/ft	16000	8" @ 15 lb/ft		

## AXLE SPECIFICATIONS (rubber ride suspension)

GVWR	axles
12000 lb	6000 lb with electric brakes & easy lube spindles
14000 lb	7000 lb with electric brakes & easy lube spindles
16000 lb	8000 lb with electric brakes & oil bath hubs

# **WEIGHT SPECIFICATIONS**

Bumper Pull				Gooseneck			
Length	12000 GVWR	14000 GVWR	16000 GVWR	12000 GVWR	14000 GVWR	16000 GVWR	
20'	3340 lbs	3360 lbs	3800 lbs	4120 lbs	4140 lbs	4580 lbs	
22'	3680 lbs	3700 lbs	4140 lbs	4460 lbs	4480 lbs	4920 lbs	

