







FH+10 SERIES



ULH+6 SERIES





ULH SERIES



UDC SERIES





CR SERIES







STANDARD SPECIFICATIONS

deck height	low profile:	33" (optional)	36" (standard)
overall width	100"		
brakes	electric brakes, all wheels		
torsion axles	on 7k and 8k		
stake pockets	1/4" x 2" x 4"		
tire	16" radial 10 ply rated		
wheel	16", 8-bolt		
jack(s)	10,000 lb. spring-loaded foot		
coupler	2 ⁵ /16 ^{ll} adjustable		
cross-members	3" channel, approx. 24" spacing		
	on 9k and 10k, approx. 16" spacing		
side rails	6" channel w/ rub rail & stake pockets,		
	approx. 24" spacing		
safety chains	3/8" w/ latch hook		
lights & wiring	LED lights with sealed wire harness		
	moisture-resistant connectors		
floor	2" treated yellow pine		
ramp construction	4" channel	x 2" x 3" x ³ /16	'angle
5' adjustable dovetail		spring-loaded ramps	
breakaway kit (with charger)		side turn signals	
steps for deck access		tool box w/lid - diamond plate	

OPTIONS

OPTIONS	
pintle ring	
tool box - under body (mounts under deck on side)	
25/16" heavy-duty coupler	
no dovetail or ramps	
winch mounting plate (mounts between gooseneck beams)	
axle upgrade 7k to 8k with 17.5" radial tires (17,000 GVWF	۲)
axle upgrade 7k tandem to 7k tri-axle (20,000 GVWR)	
axle upgrade 10 k dual G D to 10 k dual H D	
axle upgrade disk brakes on 10k (hydraulic brakes)	
torsion stabilizer	
spare tires and wheels	
dovetail jack	
dual/single-speed jacks	
one/two-speed jack or dual/two-speed jacks	
electric over hydraulic brakes	
vertical ramp bars	
third center ramp	
no ramps	
100" x 80" deck over gooseneck	

angle on dovetail, in place of wood

WEIGHT SPECIFICATIONS

	7k gooseneck	7k pintle ring	10k gooseneck	10k pintle ring
16'	4900 lbs.	4300 lbs.	5400 lbs.	4800 lbs.
18'	5100 lbs.	4600 lbs.	5800 lbs.	5300 lbs.
20'	5400 lbs.	4800 lbs.	6300 lbs.	5700 lbs.
22'	5700 lbs.	5100 lbs.	6800 lbs.	6200 lbs.
24'	5900 lbs.	5400 lbs.	7200 lbs.	6800 lbs.
26'	6200 lbs.	5600 lbs.	7700 lbs.	7100 lbs.

All weights include 5' dovetail and ramps.
If purchasing without dovetail, deduct 1000 lbs.

If substituting 8k axles for 7k, add 300 lbs.

Top deck option weighs approximately 960 lbs.


FRAME & AXLE SPECIFICATIONS

	single wheel	single wheel - 17,000/dual wheel - 20,000
	14,500 GVWR 7k torsion axle	17,000 GVWR 8k torsion axle
		20,000 GVWR 10k spring axle
16' low-profile	10" @ 12 lbs . w/8" @ 10 lbs . over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
16' standard deck	10" @ 12 lbs .	10" @ 19 lbs .
18' low-profile	10" @ 12 lbs . w/8" @ 10 lbs . over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
18' standard deck	10" @ 12 lbs .	10" @ 19 lbs .
20' low-profile	10" @ 12 lbs . w/8" @ 10 lbs . over axles	10" @ 19 lbs. w/8" @ 15 lbs. over axles
20' standard deck	10" @ 12 lbs.	10" @ 19 lbs .
22' low-profile	10" @ 12 lbs . w/8" @ 10 lbs . over axles	10" @ 19 lbs . w/8" @ 15 lbs . over axles
22' standard deck	10" @ 12 lbs .	10" @ 19 lbs .
24' standard deck	10" @ 19 lbs .	10" @ 19 lbs .
26' standard deck	10" @ 19 lbs.	10" @ 19 lbs.





665 North Main Street, Mansfield, Ohio 44902 Phone (419)526-5222 www.moritzint.com



© 2014 Moritz International, Inc. design, specifications, and prices are subject to change without notice. Printed in U.S.A.