

PINTLE HITCH DECKOVER EQUIPMENT TRAILERS - MODEL P

PROFESSIONAL GRADE

- Treated wood deck
- 96" wood deck, 101.5" to outside of rubrail
- Cold form continuous tongue (no notching or heating) with tool tray and lockable lid
- 5' swing up ramps with support foot
- 2 5/16 adjustable coupler or pintle ring (same price for either)
- 12,000 lb. drop foot jack
- Stake pockets and rubrail, self-charging break away kit, safety chains, DOT reflective tape, and all rubber mounted sealed beam LED lighting with U.S. made sealed modular harness with 5 year warranty
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

10,000 GVWR - 8" I-BEAM 20' (16'+4')

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75R15 load range "D" 8 ply rating RADIAL tires
- 8" I-beam frame (W8 x 10) • 4" side rails
- 3" channel cross members 20" spacing
- Metal plate over wheels for lowest possible loaded deck height (30")

12,000 GVWR - 8" I-BEAM 22' (18'+4')

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST235/80R16 load range "E" 10 ply rating RADIAL tires
- 8" I-beam frame (W8 x 10) • 6" side rails
- 3" channel cross members 16" spacing
- Metal plate over wheels for lowest possible loaded deck height (33")



SIZE	PRICE

15,000 GVWR - 10" I-BEAM 23' (19'+4') - 23' (18'+5')

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- ST235/80R16 load range "E" 10 ply rating RADIAL tires
- 10" I-beam frame (W10 x 12) • 6" side rails
- 3" channel cross members 16" spacing
- Metal plate over wheels for lowest possible loaded deck height (33")

GENERAL DUTY 23' (19'+4') • 23' (18'+5')

- Treated wood deck
- 96" wood deck, 101.5" to outside of rubrail
- 8" I-beam frame (W8 x 10)
- 4" side rails
- 3" channel cross members 24" spacing
- Cold form continuous tongue (no notching or heating) with tool tray
- 5' swing up ramps with support foot
- 2 5/16 adjustable coupler or pintle ring (same price for either)
- 12,000 lb. drop foot jack
- Stake pockets and rubrail, self-charging break away kit, safety chains, DOT reflective tape, and all rubber mounted
- sealed beam lighting with conventional wiring with gel filled connectors.
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

10,000 GVWR - 8" I-BEAM 20' (16'+4')

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75D15 load range "D" 8 ply rating BIAS tires
- Metal plate over wheels for lowest possible loaded deck height (30")

12,000 GVWR - 8" I-BEAM 22' (18'+4')

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- 750/16 load range "F" 12 ply rating BIAS tires
- Metal plate over wheels for lowest possible loaded deck height (34")

TOM'S AUTO SERVICE
12645 STATE HWY. 8
TITUSVILLE, PA 16354
PH. 814-827-1073



SIZE	PRICE

14,000 GVWR - 8" I-BEAM 22' (18'+4')

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- 235/80R16 load range "E" 10 ply rating RADIAL tires
- Metal plate over wheels for lowest possible loaded deck height (33")

GENERAL DUTY AND PROFESSIONAL GRADE P OPTIONS

- Cleated dovetail • Pop-up dovetail • Spring assist on ramps
- Lay flat - wedge shaped ramps (5 foot dovetail only)
- Third lay flat ramp • Heavy duty split gate with spring assist
- Third ramp • Replacement ramp • Dual jacks • Dual speed jacks
- Spare Mount • Spare tire and wheel • Load range "G" spare tire
- Upgrade to all steel belted load range "G" tires • Call for additional lengths

GENERAL DUTY P OPTIONS

- Sealed modular wiring harness • LED lighting
 - Lockable lid on tool tray • 16" cross member spacing
 - 15" radial tire upgrade • 16" radial tire upgrade
- THESE OPTIONS COMBINED MAKE UP THE PROFESSIONAL GRADE PACKAGE. PROFESSIONAL GRADE PACKAGE INCLUDES HEAVIER MAIN FRAME NOT LISTED AS AN OPTION.**